

GPS Bluetooth Receiver



GPS-BT74S

High Performance High Sensitivity GPS Bluetooth® Receiver

GENERAL DESCRIPTION

GPS-BT74S Bluetooth GPS receiver, a total solution of GPS Bluetooth wireless technology, is dedicated design for the user who is usually carry the portable device such as PDAs/smart phones all the time. GPS-BT74S allows from 15 hours continuous use to stand-by time up to one week with a single battery charge. GPS-BT74S Bluetooth GPS receiver works to all Bluetooth smart phones, lap-top, PDA regardless of brand in an operating range of more than 10 meters. The high performance high sensitivity GPS-BT74S is an ideal receiver to be used in any strict weather condition, so to easily find your way.

APPLICATIONS

- Automotive
- Fleet management/Asset tracking
- Personal/Portable Navigation (PDA, Pocket PC etc.)
- Location Based Services enabled devices
- Sports and Recreation
- Geographic Surveying

KEY PRODUCT FEATURES

- 20 channels “All-In-View” tracking
- Cold/Warm/Hot start time: 42/38/1 sec. (average)
- Superior sensitivity: -159dBm tracking
- Reacquisition time: 0.1 sec.
- Build-in ceramic patch antenna
- Build-in rechargeable Li-ion battery
- Support standard NMEA-0183 at 38400 bps baud rate
- Compatible with Bluetooth devices with Serial Port Profile (SPP)
- Ultra low power consumption: 15 hours continuous use to stand-by time up to one week by 1100mAh battery
- Time to full recharge: within 3 hours
- 3 LEDS display all GPS, Bluetooth and power status
- Size: 81.0 (L) X 43.0 (W) X 17.6 (H) mm
- Weight: 60g (battery included)
- Non-slip back pad for a secure placement

GPS Bluetooth Receiver

SPECIFICATIONS

GPS Features

Chipset	SiRF Star III
Frequency	L1, 1575.42MHz
C/A Code	1.023MHz chip rate
Channels	Supports 20 channels
Antenna (Internal)	Built-in low noise antenna

Sensitivity

To – 159dBm Tracking, Superior Urban Canyon Performance

Time to First Fix (TTFF)

Cold Start	42 sec, average
Warm Start	38 sec, average
Hot Start	1 sec, average
Reacquisition	0.1 sec
Update rate	1 Hz (max.)

Accuracy

Position	5 – 25m CEP without SA
Velocity	0.1m/sec, without SA
Time	1 μ s synchronized to GPS time

Power

Built-in rechargeable 1100mAh Li-ion battery and 5V DC input	
Operation Current	<75mA (Typical)
Operation Time	15hrs, fully charged, in continuous mode
Charging time	3.0hrs. (Typical)

Environmental Characteristics

Operating Temperature	- 10°C to + 60°C
Storage Temperature	- 20°C to + 85°C

Datum

WGS-84

Dynamic Conditions

Altitude	<18,000 m (60,000feet)
Velocity	<515 m/s (1000 knots)
Acceleration	<4G
Motional Jerk	20m/sec ³ max.

Interface

Communication Protocol: Communicate with host platform via Bluetooth (class 2) serial port profile

Bluetooth communication distance 10meters (Typical)

GPS Protocol: Default: NMEA-0183 - GGA, GSA, GSV,

RMC

Data bit: 8, stop bit: 1(Default)

Device Size and Weight

81.0 (L) X 43.0 (W) X 17.6 (H) mm
3.19 (L) X 1.69 (W) X 0.69 (H) inch
60g (battery included)

Accessories

Car charger (12V in, 5V output)
AC adaptor (5.3V output, 500mA)